

490-515W

POWER RANGE

Houmen Solar

HNM7-SHDB132 Series

Houmen Solar 10BB HALF-CELL Bifacial
Monocrystalline P - TYPE Solar Module

KEY FEATURES



Excellent Cells Efficiency

MBB technology reduce the distance between busbars and finger grid line which is benefit to power increase.



Anti PID

Ensured PID resistance through the quality control of cell manufacturing process and raw materials.



Bifacial Technology

Up to 25% additional power gain from back side depending on albedo.




Better Weak Illumination Response

More power output in weak light condition, such as haze, cloudy, and early morning.




Adapt To Harsh Outdoor Environment

Resistant to harsh environments such as salt, ammonia, sand, high temperature and high humidity environment.



LINEAR PERFORMANCE WARRANTY



IEC61730, UL61730
ISO9001:2015: Quality Management System
ISO14001:2015: Environment Management System
ISO45001:2018 Occupational health and safety management systems



12 YEARS PRODUCT WARRANTY



25 YEARS OUTPUT GUARANTEE

515W

MAXIMUM POWER OUTPUT


21.69%

MAXIMUM EFFICIENCY

70±5%


BIFACIALITY

DIMENSIONS OF PV MODULE(mm)




*Remark: customized frame color and cable length available upon request.

I-V CURVES OF PV MODULE(490W)



P-V CURVES OF PV MODULE(490W)



ELECTRICAL CHARACTERISTICS

Module Type	HNM7-SHDB132-490/M		HNM7-SHDB132-495/M		HNM7-SHDB132-500/M		HNM7-SHDB132-505/M		HNM7-SHDB132-510/M		HNM7-SHDB132-515/M	
STC/NMOT	STC	NMOT										
Nominal Power Watt Pmax(W)*	490	366.40	495	370.00	500	373.60	505	377.40	510	381.10	515	384.70
Maximum Power Voltage Vmp(V)	37.80	35.10	38.00	35.30	38.20	35.50	38.40	35.70	38.60	35.90	38.80	36.10
Maximum Power Current Imp(A)	12.97	10.43	13.03	10.48	13.09	10.52	13.16	10.57	13.22	10.61	13.28	10.66
Open Circuit Voltage Voc(V)	45.40	42.40	45.60	42.60	45.80	42.80	46.00	43.00	46.20	43.10	46.40	43.30
Short Circuit Current Isc(A)	13.72	11.08	13.78	11.13	13.84	11.18	13.90	11.22	13.96	11.27	14.02	11.32
Module Efficiency (%)	20.64		20.85		21.06		21.27		21.48		21.69	

*STC (Standard Test Condition): Irradiance 1000W/m², Module Temperature 25±2°C, AM 1.5.

*NMOT: Irradiance 800W/m², Ambient Temperature 20°C, AM 1.5, Wind Speed 1m/s.

BIFACIAL OUTPUT-REARSIDE POWER GAIN

Maximum Power (Pmax) 5%	515Wp	520Wp	525Wp	530Wp	536Wp	541Wp
Maximum Efficiency STC (%)	21.65%	21.90%	22.14%	22.38%	22.63%	22.87%
Maximum Power (Pmax) 15%	564Wp	569Wp	575Wp	581Wp	587Wp	592Wp
Maximum Efficiency STC (%)	23.71%	23.98%	24.25%	24.51%	24.78%	25.05%
Maximum Power (Pmax) 25%	613Wp	619Wp	625Wp	631Wp	638Wp	644Wp
Maximum Efficiency STC (%)	25.78%	26.07%	26.36%	26.65%	26.93%	27.22%

MECHANICAL DATA

Solar cells	Mono P-Type
Cells orientation	132 (6x22)
Module dimension	2094x1134x30 (With Frame)
Weight	25.0±1Kg
Glass	3.2mm, High Transmission, AR Coated Tempered Glass
Junction Box	IP68, 3 diodes
Cables	4 mm², 1200mm (With Connectors)
Connectors	MC4

*Please refer to regional datasheet for specified connector.

WORKING CONDITIONS

Maximum System Voltage	1500VDC
Operating Temperature	-40°C~+85°C
Maximum Fuse Rating	30A
Rear Side Mechanical Load	2400Pa
Front Side Mechanical Load	5400Pa
Safety Class	Class II

TEMPERATURE RATINGS

NMOT	44°C±2°C
Temperature coefficient of Pmax	-0.35%/°C
Temperature coefficient of Voc	-0.29%/°C
Temperature coefficient of Isc	0.05%/°C
Refer. Bifacial Factor	70±5%

PACKAGING CONFIGURATION

Container	40'HQ
Piece/Box	36
Piece/Container	792

*Customized packaging is available upon request.

Revised in Sep 2023 1st Edition. Specifications included in this datasheet are subject to change without notice. Hounen Solar reserves the right of final interpretation.